

The GroBarLED[™] Linear Luminaire

HIGH-OUTPUT, LIGHT-WEIGHT, ENERGY EFFICIENT LED GROW SOLUTION



Powerful, light-weight and energy efficient with extremely low heat, the new GroBar is ideal for a variety of horticultural applications. One 4' linear luminaire can replace two HO 54W T5 bulbs with better spectrum for your plants. Weighing in at only 19 ounces, the GroBar is so lightweight that it can be mounted directly to the ceiling, racks or mounted in groups of three with our brackets. A three light kit has higher par levels and 60% less power usage than T5 fixtures that use six 54W HO bulbs. Wet-rated and available in two and four-foot lengths, the GroBar is the ideal choice of horticulturists for seed, clone and veg.

Lightweight Design: Low-profile, robust, polymer construction provides quick and easy installation of this high-output light source

Cost Effective: Costs 50% less per input watt than other LED grow linears/bars

Energy-Efficient: As much as 60% energy savings compared to fluorescent and HID lighting options

Mountable: Ships with flush mount hardware clips for fast and clean surface mounting. Optional brackets available to create 3 light fixture.

Flexibility: Easy to connect multiple fixtures on one circuit.



PRODUCT SPECIFICATIONS

SPECIFICATIONS ¹	2 FT GROBAR	4 FT GROBAR
Color Temperature	4000K and 5000K (3000K Coming Soon)	
PAR Output	30 $\mu\text{mol/s}$	60 $\mu\text{mol/s}$
Beam Angle	100°	
Power Consumption	14.5 W	29 W
Power Factor	≥ 0.9	
PAR Efficacy	2.1 $\mu\text{mol/J}$	
Dimmable	No	
Input Voltage	110-277 VAC	
Dimensions (l x w x h)	24" x 1.87" x 1.11"	48" x 1.87" x 1.11"
Weight	Fixture 0.46 lbs (0.21 kg) with cord 0.93 lbs (0.42 kg)	Fixture 0.73 lbs (0.33 kg) with cord 1.2 lbs (0.55 kg)
Housing	Polycarbonate	
Power Connections	Multiple Available	
Lumen Maintenance ^(L)	50,000 hours	
Mounting	Surface mount hardware included *Various mounting brackets options available *Call us for custom design of your space	
Certifications	ETL, FCC, RoHS	ETL, FCC, RoHS, DLC
Environment	Wet-rated, IP65	
Warranty	5 Year Limited	

¹ Specifications and values supplied are nominal and are subject to change without notification

ORDERING INFORMATION

For pricing or ordering information, please email us at sales@vividgro.com or call us at 877-999-5742.



VividGro_GroBar_SpecSheet_REVC



Tel: +52 55 5251 2008 / info@bhpenergy.mx / ventas@bhpenergy.mx
©2017 BHP Energy México. Todos los derechos reservados. www.bhpenergy.mx